


For greater coverage and IP protection



- The smallest Sorrento - also available in Maxi, Midi and Mini sizes
- Wide beam angle of 75°
- Dust and water protected with IP54 rating
- Low unified glare rating (UGR)
- Suitable for commercial, facility and hospitality applications

Product info

System Lumen Range	1200lm
System Power	13W
Forward Current	350mA
System Efficacy	92lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Fixed Recessed
IP Rating	IP54
Dimming Type	Non-Dimmable, Phase-Cut Dimmable, DALI Dimmable
Accessories	Without Accessory
Custom Dimming Type	Available on request



Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 4000K
Beam Angle	75°
Custom Colour Temperature (CCT)	Available on request

Packaging

Box Weight	0.26Kgs
Box Dimensions L x W x H mm	155mm x 155mm x 160mm
Boxes per Carton	12
Carton Weight	3.5Kgs
Carton Dimensions L x W x H mm	485mm x 330mm x 345mm

Sorrento Tiny

DOWNLIGHT | Product code MD20

MONDOLUX™
mondolux.com.au

Polar distribution diagrams

