

Cannes Midi DOWNLIGHT



Product Code

MD28









Technical Description

Surface mount sophisticated statement...

- Part of the Mondolux Cannes family, with our signature Cross-Beam Lens technology for excellent efficacy and soft cut-off
 An elegant architectural downlight, ideal for residential, architectural and commercial applications
 Baffle finish options available: White, Black and Gold

- Configure with Honeycomb accessory to further minimise glare, improve visual comfort or increase exposure protection
 Also available in Mini and Maxi size options, and in surface mounted and suspended versions
 If you require a customised version of this product, please contact us

Electrical Specifications

System Power	20W
Input Voltage	240V
Control Type	0-10V, Phase-Cut, DALI, Casambi, DMX
System Efficacy (max.)	83lm/W
Power Factor	> 0.9
Photometric Info	


Luminaire Lumens	1650lm
CRI	CRI90
ССТ	2700K. 3000K. 4000K
Beam Angle	16°, 30°, 50°
Lumen Maintenance	>55, 400hrs (L70 B10)
MacAdam Step	3 Step
CCT Beam Angle Lumen Maintenance	2700K, 3000K, 4000K 16°, 30°, 50° >55, 400hrs (L70 B10)

Physical Characteristics

Installation Method	Surface Mounted
Trim Finish	White, Black
IP Rating / IK Rating	IP20
Accessories	Black Baffle, Black Baffle and Honeycomb, Gold Baffle, Gold Baffle and Honeycomb, White Baffle, White Baffle and Honeycomb
Fitting Material	Aluminium








Ø75mm

150mm

Cannes Midi 50°



Cannes Midi 30°

