MONDOLUX

DC LOW VOLTAGE

RoHS

 $\langle || \rangle$

CE

Genoa Midi



Product Code

MV78

Technical Description

Out of sight, front of mind

- Part of the Mondolux Pacto DC48V low-voltage range, and the middle member of the Genoa family
 A discrete in-track linear luminaire that can be used to create continuous lines of light, with in-track installation to reduce visual bulk and maintain clean lines
 Wide beam angle of 110° for excellent uniformity, making it ideal for general area illumination
 Modular 48V click-in system for flexibility and easy installation
 Also available in <u>Mini</u> and <u>Maxi</u> sizes
 Non-dimmable and PWM DALL control options (Casambi Wireless Control available upon request)
 If you cauring a curstemined version of this product places control to the second to


- If you require a customised version of this product, please $\underline{\mbox{ contact us}}$

Electrical Specifications	
System Power	11W
Input Voltage	48V DC
Control Type	ON/OFF, DALI
System Efficacy (max.)	71lm/W

Photometric Info

Luminaire Lumens	780lm
CRI	CRI80
ССТ	3000K, 4000K
Beam Angle	110°

Physical Characteristics	
Installation Method	DC-Track Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP20
Fitting Material	Aluminium



Polar Distribution Diagrams

Genoa Midi 110°

