MONDOLUX

RoHS

CE

&

OUTDOOR

Cento 360





MO83

Technical Description

Sleek style and durability...

- Outdoor decklight designed for commercial outdoor use
 Highly efficient, robust performance
 Exceptional IP67 and IK06 ratings with CRI90 as standard and a 5-year warranty*
 Aluminium housing with UV stabilised double layer powder coating in matte black finish (316 Stainless Steel grade available on request)
 <u>Cento 90</u> and <u>Cento 180</u> variants available
 Local stock availability
 If you restorpised version of this product places, contact us.


If you require a customised version of this product, please <u>contact us</u>
 *Please see Warranty Terms & Conditions for further information

Electrical Specifications

Electrical Specifications	
System Power	3.5W
Input Voltage	24V DC
Control Type	ON/OFF
System Efficacy (max.)	51lm/W
Photometric Info	
Luminaire Lumens	180lm
CRI	CRI90
ССТ	3000K
Beam Angle	185°
Lumen Maintenance	>51, 850hrs (L70 B10)
MacAdam Step	3 Step

Physical Characteristics

Installation Method	Fixed Recessed
Trim Finish	Black
IP Rating / IK Rating	IP67/ IK06
Weight	0.3Kgs
Fitting Material	Aluminium



Ø42mm

Polar Distribution Diagrams

Cento360 185°

