

## Cori Mini

## DOWNLIGHT

## Product Code

MD58



## Technical Description

## The all-weather wonder...

- Specifically designed for commercial outdoor applications
- Robust performance with exceptional IP65 and IK09 ratings
- UV-stabilised matte finish (Marine Grade Powdercoat and other finishes available on request)
- With a 5-year warranty\* as standard, this downlight will go the distance on your projects
- Also available in Tiny and Midi size options
- Local stock availability
- Available in 15°, 25° and 40° optics
- If you require a customised version of this product, please [contact us](#)

\*Please see Warranty Terms &amp; Conditions for further information.

## Electrical Specifications


System Power	20W
Input Voltage	240V
Control Type	ON/OFF, DALI, Casambi
System Efficacy (max.)	83lm/W
Power Factor	> 0.9

## Photometric Info

Luminaire Lumens	1650lm
CRI	CRI80
CCT	2700K, 3000K, 4000K
Beam Angle	15°, 25°, 40°
Lumen Maintenance	> 63, 200hrs (L70 B10)
MacAdam Step	3 Step


## Physical Characteristics

Installation Method	Fixed Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP65
Fitting Material	Aluminium




## Polar Distribution Diagrams

Cori Mini 15°



Cori Mini 25°



Cori Mini 40°

